

ALBATROSS STOCK INDICATOR



Date: March 16 2021

Main location: EUROPE

Location	Volume and T code	Quantity	Supplementary Notes
Lined Equipment			
Moerdijk	17,5 cbm, T20	3	top only, full WW, bottom outlet provision
	24 cbm, T14	2	24 cbm, Chemline, T14, top only, handrail, full walkway
21 cbm			
Moerdijk	21 cbm, T14	2	T14, 10 bar design pressure, bottom discharge provision, air inlet DN40 ball valve, top discharge 3" with DN50 ball valve, DN50 ball valve, DN80 ball valve
Moerdijk	21 cbm, T11	15	21 cbm, T11
Moerdijk	21 cbm, T20	3	full WW, DN50 top discharge, DN80 top discharge provision, DN40 airline, 3" relief valve provision, 3" relief valve assembly
22.5 cbm			
Moerdijk	22.5 cbm T22	12	with U stamp
24 cbm			
Moerdijk	24 cbm, T11 bottom outlet	3 + 4 food	T11, bottom outlet 3" NB 45° highlift footvalve and 3" flanged butterfly valve, top outlet 3" flanged butterfly valve, 3"/DN80 syphon tube, full WW
25 cbm			
Moerdijk	25 cbm, T14	1	top only, T14, handrail, 3" bottom outlet provision, 1,5" BSP airline DN40 ball valve, top outlet 3"/DN80 butterfly valve, spare 3"/DN80, spare 2"/DN50
26 cbm			
Moerdijk	26 cbm, T11	13	mixed, T11, full WW, handrail, syphon tube, 3" BSP bottom outlet, 3"/DN80 butterfly on top outlet, 1,5"/DN40 BSP airline, 2"/DN40 spare, 3"/DN80 spare
St. Petersburg (RUS)	26 cbm, T11	45	T11, full WW, handrail, 3" BSP bottom discharge 3" NB 45° highlift footvalve and 3" clamped butterfly valve, DN80 top discharge blind flange, 3"/DN80 spare provision, Safety Relief Provision
Shahunja (RUS)	26 cbm, T11	25	T11, full WW, handrail, 3" BSP bottom discharge 3" NB 45° highlift footvalve and 3" clamped butterfly valve, DN80 top discharge blind flange, 3"/DN80 spare provision, Safety Relief Provision

Oberhausen	26 cbm, T11	14 food	mixed, T11, full WW, handrail, syphon tube, 3" BSP bottom outlet, 3"/DN80 butterfly on top outlet, 1,5"/DN40 BSP airline, 2"/DN40 spare, 3"/DN80 spare
30 cbm			
Moerdijk	30 cbm, T11	2	bottom outlet 3" with butterfly valve, air inlet DN50 and DN40, top discharge 3" provision, 3" flange relief valve, 2 x DN80 spare provision
T50			
Moerdijk	24.3 cbm, 27.5 Bar	6	T50, Liquid Line DN50 bottom valve, Gas Line DN50 bottom valve, Safety Relief Valve DN80, manometer, thermometer, Sun Shield, Surface Treatment
Moerdijk	34.5 Bar	3	T50 34,5 Bar
Moerdijk	13.8 Bar	2	T50 13,8 Bar
T75			
Oberhausen	T75, 20 cbm	20	T75 20 cbm
Oberhausen	T75, 45.5 cbm	1	T75 45.5 cbm
K0			
St. Petersburg (RUS)	29.5 cbm	6	increased capacity for non dangerous cargo
Oberhausen	29.5 cbm	4	increased capacity for non dangerous cargo