

ALBATROSS STOCK INDICATOR



Date: September 7 2020

Main location: EUROPE

Location	Volume and T code	Quantity	Supplementary Notes
Lined Equipment			
Moerdijk	17,5 cbm, T20	3	top only, full WW, bottom outlet provision
	24 cbm, T14	2	24 cbm, Chemline, T14, top only, handrail, full walkway
21 cbm			
Moerdijk	21 cbm, T14	2	T14, 10 bar design pressure, bottom discharge provision, air inlet DN40 ball valve, top discharge 3" with DN50 ball valve, DN50 ball valve, DN80 ball valve
24 cbm			
Moerdijk	24 cbm, T11 bottom outlet	3	T11, bottom outlet 3" NB 45° highlift footvalve and 3" flanged butterfly valve, top outlet 3" flanged butterfly valve, 3"/DN80 syphon tube, full WW
25 cbm			
Moerdijk	25 cbm, T11	5	T11, handrail, full WW, 3" BSP bottom outlet, 1,5" BSP airline 1,5" ball valve, 3" 2" spare provision, 3" spare provision
Moerdijk	25 cbm, T14	1	top only, T14, handrail, 3" bottom outlet provision, 1,5" BSP airline DN40 ball valve, top outlet 3"/DN80 butterfly valve, spare 3"/DN80, spare 2"/DN50
26 cbm			
Moerdijk	26 cbm, T11	56	T11, full WW, handrail, 3" BSP bottom discharge 3" NB 45° highlift footvalve and 3" clamped butterfly valve, DN80 top discharge blind flange, 3"/DN80 spare provision, Safety Relief Provision
St. Petersburg (RUS)	26 cbm, T11	10	T11, full WW, handrail, 3" BSP bottom discharge 3" NB 45° highlift footvalve and 3" clamped butterfly valve, DN80 top discharge blind flange, 3"/DN80 spare provision, Safety Relief Provision
Shahunja (RUS)	26 cbm, T11	20	T11, full WW, handrail, 3" BSP bottom discharge 3" NB 45° highlift footvalve and 3" clamped butterfly valve, DN80 top discharge blind flange, 3"/DN80 spare provision, Safety Relief Provision
30 cbm			

Moerdijk	30 cbm, T11	5	bottom outlet 3" with butterfly valve, air inlet DN50 and DN40, top discharge 3" provision, 3" flange relief valve, 2 x DN80 spare provision
35 cbm			
Moerdijk	35 cbm, T11	2	T11, full WW, handrail, 3" BSP bottom outlet, 3" top discharge provision, 2" airline assembly 2" flanged airline ball valve, 1.5" air inlet 1.5" BSP ball valve, DN50 spare provision, DN80 spare provision
T50 27,5 Bar			
Moerdijk	24.3 cbm T50	1	T50, Liquid Line DN50 bottom valve, Gas Line DN50 bottom valve, Safety Relief Valve DN80, manometer, thermometer, Sun Shield, Surface Treatment
T75			
Oberhausen	T75, 20 cbm	20	T75 20 cbm
Oberhausen	T75, 45.5 cbm	1	T75 45.5 cbm